

Crumb Rubber Tiles and Rolls

Specification Sheet

Multi-functional rubber flooring designed for use in residential, commercial or industrial applications where added comfort under foot is needed. Cycle flooring can be used on indoor or outdoor applications where enhanced walking comfort and slip resistance is desired.

Construction: Crumb Rubber Tile and Roll

Nominal Dimensions Tile: 34 1/4" x 34 1/4"

Nominal Dimensions Roll: 48" x 49 1/2'

Thickness: 5/16"

Quantity per Pallet: 100 Tiles / 6 Rolls

Weight Per Tile/Roll: 14lbs (tiles / 310lbs (rolls)

Standard	Description	Result
ASTM F3041	Classification - Bonded Crumb Rubber	Type I & II, Class A
ASTM D2047	Coefficient of Friction	>0.8
ASTM E648 (NFPA 253)	Critical Radiant Flux (radiant panel)	Unclassified. 0.10 W/cm ²
ASTM D3389	Abrasive Resistance	Passes
ASTM FF137	Flexibility	Passes
ASTM F970	Static Load Resistance	Passes, 250 PSI
ASTM F2199	Dimensional Stability	Passes
ASTM F1514	Heat Stability of Color	Passes
ASTM F925	Short Term Chemical Exposure	Passes (See ASTM 3041 Test)
ASTM E492	Impact Sound Transmission:	57 IIC
ANSI B101.1	Coefficient of Friction / Slip Resistance	> 0.6 (Dry)